



Traditional
Format
Walling

A TIMELESS ARCHITECTURAL AESTHETIC

Traditional Format walling is a timeless and sophisticated format that will never date. It's been used in buildings throughout Australia for years and has an ageless aesthetic appeal. Traditional Format walling incorporates core stone types such as sandstone, limestone and travertine.

With natural warmth and subtle colour variation these stone walling options help provide atmosphere to any space. Random lengths develop variety in arrangement while our sibling flooring range supports a sense of design continuity.

We believe that finishing is key for natural stone working effectively in a design and our L-shaped corner units offer a sense of structural depth and form that cannot be achieved with a miter joint.






Barlow



Barrimah



Broma




Scala Split

A selection of high resolution 3D textures is available on our website.


SIZES

Walling

Split Face




Sawn Face




Corners


Split Face



Sawn Face



Capping



For more downloadable imagery visit our website.

Imperial *Weight* *Packing Details*
(lbs/UOM) (UOM/crate)

Barlow

Walling

Sandblasted veneer, sawn on 5 sides

Random lengths

8" / 12" / 16" x 12"-36", ¾"

10 270 (5x54ft²)

Corners

Long side 6 ¾"-8 ½"

Short side 3 ¼"-4 ¾"

Set height 8" / 12" / 16"

Thickness ¾"

15 52 (2x26LFT)

Capping options available on request

Barrimah

Walling

Heavily distressed veneer on 5 sides, sawn on back

Random lengths

12" / 16" x 12"-27 ½", ¾"-1 ½"

15 150ft² (2x75ft²)

Corners

Heavily distressed corner veneer

L shape corner pieces

Long side 12"-16"

Short side 4 ¾"-6 ¾"

Set height 12" & 16"

Thickness ¾"-1 ½"

31 40 units

Capping

12" x 24", 2"

55 60 units

Corner Capping

Long side 12"

Short side 4"

Random Length 16"-24"

Thickness ¾"-1 ½"

23 66LF

Metric *Weight* *Packing Details*
(kg/UOM) (UOM/crate)

Barlow

Walling

Sandblasted veneer, sawn on 5 sides

Random lengths

203/305/406x305-915mm, 18mm

50 25m² (5x5m²)

Corners

Long side 170-220mm

Short side 80-120mm

Set height 203/305/406mm

Thickness 18mm

22 16LM (2x8LM)

Capping options available on request

Barrimah

Walling

Heavily distressed veneer on 5 sides, sawn on back

Random lengths

300/400x300-700mm, 20-40mm

75 14m² (2x7m²)

Corners

Heavily distressed corner veneer

L shape corner pieces

Long side 300-400mm

Short side 120-170mm

Set height 300mm & 400mm

Thickness 20-40mm

14 40 units

Capping

300x600mm, 50mm

25 60 units

Corner Capping

Long side 300mm

Short side 100mm

Random Length 400-600mm

Thickness 20-40mm

34 20LM

*All metric measurements are accurate.
All imperial measurements are nominal.*

These stones have a split, sawn, honed or heavily distressed front face, with a sawn rear and sides to help facilitate easy installation. While usually supplied in random lengths with a set height, custom sizing can be created to suit project requirements. Typically these products are adhered to a concrete or block wall with a suitable tile adhesive. Use of mechanical fixings may also be required. When working out quantities required for a wall, you need to know the face in square metres / feet to be covered and the number of lineal metres / feet of corners required. Corners units are adjusted on site to deal with random length junctions. For further information, installation tips and pricing please contact us.

<i>Imperial</i>	<i>Weight (lbs/UOM)</i>	<i>Packing Details (UOM/crate)</i>	<i>Metric</i>	<i>Weight (kg/UOM)</i>	<i>Packing Details (UOM/crate)</i>
Broma			Broma®		
Walling Heavily distressed veneer on 5 sides, sawn on back Random lengths 12" / 16" x 12"-27 1/2", 3/4"-1 1/4"			Walling Heavily distressed veneer on 5 sides, sawn on back Random lengths 300/400x300-700mm, 20-30mm		
	13	162ft ² (3x54ft ²)		65	15m ² (3x5m ²)
Corners Heavily distressed corner veneer L shape corner pieces Long side 12"-16" Short side 4 3/4"-6 3/4" Set height 12" & 16" Thickness 3/4"-1 1/4"			Corners Heavily distressed corner veneer L shape corner pieces Long side 300-400mm Short side 120-170mm Set height 300mm & 400mm Thickness 20-30mm		
	31	40 units		14	40 units
Capping 12" x 24", 2"			Capping 300x600mm, 50mm		
	55	60 units		25	60 units
Scala Split			Scala® Split		
Walling Split veneer, sawn on 5 sides Random lengths 6" / 10" / 14" x 12"-29 1/2", 1 1/4"- 3"			Walling Split veneer, sawn on 5 sides Random lengths 152/254/355x305-750mm, 30-80mm		
	19	127ft ²		91	11.795m ²
Corners Long side 6"-12" Short side 4"-6" Set height 6" / 10" / 14" Thickness 1 1/4"-3"			Corners Long side 150-300mm Short side 100-150mm Set height 152/254/355mm Thickness 30-80mm		
	13	60 units		6	60 units
Capping 12" x 24", 2"			Capping 610x305mm, 50mm		
	53	26 units		24	26 units
<i>All metric measurements are accurate. All imperial measurements are nominal.</i>					

These stones have a split, sawn, honed or heavily distressed front face, with a sawn rear and sides to help facilitate easy installation. While usually supplied in random lengths with a set height, custom sizing can be created to suit project requirements. Typically these products are adhered to a concrete or block wall with a suitable tile adhesive. Use of mechanical fixings may also be required. When working out quantities required for a wall, you need to know the face in square metres / feet to be covered and the number of lineal metres / feet of corners required. Corners units are adjusted on site to deal with random length junctions. For further information, installation tips and pricing please contact us.