

eoTM

Technifirma
Flooring

STRENGTH & DURABILITY PROVIDE EXCEPTIONAL VERSATILITY

Born out of the need for a versatile, yet consistently supplied material suitable for a broad spectrum of use, the Technifirma range is an ideal product for the most demanding of environments.

Utilising market leading technology, this range of products has homogenous performance characteristics (consistent modulus of rupture), while still maintaining variability in texture and tone similar to natural stone.


This range is extremely strong, has low water absorption characteristics, is non slip and is very easy to maintain.

Available in a range of large format sizes Technifirma is a great complement to Eco Outdoor's extensive natural stone offer.






Ambrose



Arrowmill



Ashchalk



Chimney Sweep



Culver




Harkfell



Knightrider




Lido



Mrs Char



Muddled Crow



Novara



Palma




Pegasus



Rainford



Riverdance




Rivet



Shuttle Fleck



Skywalk



Stardust



Thistledown






Wavelet

Ask us about high resolution 3D textures.

SIZES

Tiles



For more downloadable imagery visit our website.

	Imperial			Metric			Slip Resistance		
	Sizing	Weight per UOM per UOM (lbs) crate	Weight per UOM per UOM (kg) crate	Sizing	Weight per UOM per UOM (kg) crate	Weight per UOM per UOM (kg) crate	Wet Pendulum Classification	Wet Pendulum Mean BPN/SRV	Oil-wet Ramp
Ambrose	24" x 24", 3/8"	4	465.0	598x598mm, 9mm	21	43.2	P4	53	R10
	24" x 24", 3/4"	9	232.5	598x598mm, 20mm	46	21.6		46	R11
	31 1/2" x 31 1/2", 3/4"	9	289.3	798x798mm, 20mm	46	26.9		46	R11
	24" x 47 1/4", 3/8"	4	542.5	1198x598mm, 9mm	21	50.4		53	R10
	24" x 47 1/4", 3/4"	9	271.3	1198x598mm, 20mm	46	25.2		46	R11
Arrowmill	6" x 24", 3/8"	4	542.5	598x148mm, 9mm	21	50.4	P2	25	R9
	24" x 24", 3/8"	4	465.0	598x598mm, 9mm	21	43.2	P2	25	R9
	24" x 24", 3/4"	9	232.5	598x598mm, 20mm	46	21.6	P5	57	R11
	17 1/2" x 36", 3/4"	9	235.4	898x448mm, 20mm	46	21.9	P5	57	R11
	24" x 47 1/4", 3/8"	4	542.5	1198x598mm, 9mm	21	50.4	P2	25	R9
	24" x 47 1/4", 3/4"	9	271.3	1198x598mm, 20mm	46	25.2	P5	57	R11
Ashchalk	24" x 24", 3/4"	9	232.5	598x598mm, 20mm	46	21.6	P5	56	R11
	31 1/2" x 31 1/2", 3/4"	9	271.3	798x798mm, 20mm	46	26.9			
Chimney Sweep	24" x 24", 3/4"	9	232.5	596x596mm, 20mm	46	21.6			R11
Culver	24" x 24", 3/8"	4	465.0	598x598mm, 9mm	21	43.2	P4	53	R10
	24" x 24", 3/4"	9	232.5	598x598mm, 20mm	46	21.6		46	R11
	31 1/2" x 31 1/2", 3/4"	9	289.3	798x798mm, 20mm	46	26.9		46	R11
	24" x 47 1/4", 3/8"	4	542.5	1198x598mm, 9mm*	21	50.4		53	R10
	24" x 47 1/4", 3/8"	4	542.5	1198x598mm, 9mm*	21	50.4		46	R11
	24" x 47 1/4", 3/4"	9	271.3	1198x598mm, 20mm	46	25.2		46	R11
Harkfell	24" x 24", 3/4"	9	232.5	598x598mm, 20mm	46	21.6	P5	65	R11
	36" x 36", 3/4"	9	156.9	898x898mm, 20mm	46	14.6			
Knightrider	24" x 24", 3/4"	9	232.5	598x598mm, 20mm	21	21.6	P5	56	R11
	31 1/2" x 31 1/2", 3/4"	9	271.3	798x798mm, 20mm	46	26.9			
Lido	24" x 36", 3/4"	9	279.0	901x600mm, 20mm	46	25.9			R11
Mrs Char	24" x 24", 3/4"	9	248.0	596x596mm, 20mm	46	23.0			R11
	24" x 47", 3/4"	9	271.3	1197x596mm, 20mm	46	25.2			
Muddled Crow	24" x 24", 3/4"	9	232.5	596x596mm, 20mm	46	21.6			R11
	24" x 47", 3/4"	9	271.3	1197x596mm, 20mm	46	25.2			
Novara	24" x 24", 3/4"	9	232.5	598x598mm, 20mm	46	21.6	P5	56	R11
	31 1/2" x 31 1/2", 3/4"	9	271.3	798x798mm, 20mm	46	26.9			
Palma	6" x 24", 3/8"	4	542.5	598x148mm, 9mm	21	50.4	P2	25	R11
	24" x 47 1/4", 3/8"	9	542.5	1198x598mm, 9mm	21	50.4			
Pegasus	24" x 24", 3/4"	9	232.5	598x598mm, 20mm	46	21.6	P4	53	R11
	36" x 36", 3/4"	9	157.2	898x898mm, 20mm	46	14.6			
Rainford	24" x 24", 3/4"	9	232.5	598x598mm, 20mm	46	21.6	P5	56	R11
	36" x 36", 3/4"	9	156.9	898x898mm, 20mm	46	14.6			
Riverdance	24" x 24", 3/4"	9	232.5	596x596mm, 20mm	46	21.6			R11
	24" x 47", 3/4"	9	271.3	1197x596mm, 20mm	46	25.2			
Rivet	24" x 24", 3/8"	4	465.0	598x598mm, 9mm	21	43.2	P4	53	R10
	24" x 24", 3/4"	9	232.5	598x598mm, 20mm	46	21.6		46	R11
	31 1/2" x 31 1/2", 3/4"	9	289.3	798x798mm, 20mm	46	26.9		46	R11
	24" x 47 1/4", 3/8"	4	542.5	1198x598mm, 9mm	21	50.4		53	R10
	24" x 47 1/4", 3/4"	9	271.3	1198x598mm, 20mm	46	25.2		46	R11

* Note two Culver 1198x598x9mm on offer with different finishes: R10 and R11

All metric measurements are accurate. All imperial measurements are nominal.

Given the high level of dimensional accuracy, typically these tiles can be laid with a suitable tile adhesive / thin set bed.

Refer to installation tips for further information. For further information, installation tips and pricing please contact us.

	Imperial			Metric			Slip Resistance				
	Sizing	Weight per UOM	per UOM (lbs) per crate	Sizing	Weight per UOM (kg)	per UOM per crate	Wet Pendulum Classification	Wet Pendulum Mean BPN/SRV	Oil-wet Ramp		
Shuttle Fleck	24" x 24", 3/4"	9	232.5	598x598mm, 20mm	46	21.6	P5	56	R11		
	31 1/2" x 31 1/2", 3/4"	9	289.3	798x798mm, 20mm	46	26.9					
Skywalk	24" x 24", 3/4"	9	232.5	598x598mm, 20mm	46	21.6	P4	53	R11		
	36" x 36", 3/4"	9	157.2	898x898mm, 20mm	46	14.6					
Stardust	24" x 24", 3/4"	9	232.5	598x598mm, 20mm	46	21.6	P4	53	R11		
	36" x 36", 3/4"	9	157.2	898x898mm, 20mm	46	14.6					
Thistledown	12" x 47 1/4", 3/4"	9	279.0	1198x298mm, 20mm	46	25.9	P4	46	R11		
	24" x 47 1/4", 3/8"	4	542.5	1198x598mm, 9mm	21	50.4				53	R10
	24" x 47 1/4", 3/4"	4	271.3	1198x598mm, 20mm	46	25.2					
Wavelet	12" x 47 1/4", 3/4"	9	279.0	1198x298mm, 20mm	46	25.9	P4	46	R11		
	24" x 47 1/4", 3/8"	4	542.5	1198x598mm, 9mm	21	50.4				53	R10
	24" x 47 1/4", 3/4"	9	271.3	1198x598mm, 20mm	46	25.2					

* Note two Culver 1198x598x9mm on offer with different finishes: R10 and R11

All metric measurements are accurate. All imperial measurements are nominal.

Given the high level of dimensional accuracy, typically these tiles can be laid with a suitable tile adhesive / thin set bed.

Refer to installation tips for further information. For further information, installation tips and pricing please contact us.